




STRAIGHT SLOTTED GRATE




RADIUS SLOTTED GRATE



FABRICATION NOTES:

1. Drawing Represents Standard Shape & Sizes
2. Slotted Grates Can be Customized Per Individual Project
3. Slotted Grates can be Fabricated with Radius (2'-0" Min. Radius
4. Width Dimensions Varies from 8" to 18" in Total Slotted Grate Width



INSIDE / OUTSIDE SLOTTED GRATE CORNER

NOTES

1. 6,500 P.S.I. Design Mix @ 28 Days
2. ASTM C-1364 for Cast-Stone - 6% Water Absorption
3. Specification for Cast Stone 04720
4. Available in Over 85 Colors & All Standard Kerckhoff Textures
5. All Concrete is Computer Batched for Consistency w/ integral Water Proofing Admix.
6. All Concrete is Hand Placed so Colors & Textures do Vary
7. Abrasion and Mildew Resistant
8. All Slotted Grates are Reinforced w/ Galvanized Steel
9. 21 Sq. In. Open Area per 12" Wide Grate
10. Meets VGB Requirements
11. Meets ADA Fast Pool Requirements for Slip Resistant

D.C. KERCKHOFF COMPANY

SLOTTED GRATES



PLANT CERTIFIED



CONCRETE HARDSCAPE SOLUTIONS

1455 SW 4th Ave,
Delray Beach, FL 33444
(239) 597-7218